


Notes:

1. Raceway of inner & outer ring induction hardened. hardness: 55~62HRC  
Depth ≥ 3.5mm
2. Inner & outer ring quenched & tempered, hardness: 207~262HB

Gear Data				Design		Check		Model		Weight																										
Module	m	6	Gear heat treatment requirements		Date	Approve		013.30.710		120kg																										
Teeth no	z	96	HRC		Qty	Size	Axial clearance	Name		Scale																										
Teeth pressure angle	α	20°	Precision (GB10095-88)	10	Inner ring mounting hole	24	Φ18	Radial clearance	Slewing Bearing																											
Modification coefficients	x	+0.5			Outer ring mounting hole	24	Φ18	Material		Total 1 page																										
Reduction coefficients	km	1.2			Oil hole	4	M10x1	50Mn		The 1st page																										
Pitch diameter	d	576							<p style="text-align: center;"><b>XUZHOU WANDA SLEWING BEARING CO.,LTD</b></p>  <p>Fax: +86 516 83309366 Fax: +86 516 83915766 http://www.slew-bearing.com</p>																											
								<p>machine tolerances without notes</p> <table border="1"> <tr> <td>≤200</td> <td>≤500</td> <td>≤710</td> <td>≤1120</td> </tr> <tr> <td>±0.30</td> <td>±0.40</td> <td>±0.50</td> <td>±0.65</td> </tr> <tr> <td>≤1600</td> <td>≤2000</td> <td>≤2500</td> <td>≤3150</td> </tr> <tr> <td>±0.80</td> <td>±0.95</td> <td>±1.10</td> <td>±1.35</td> </tr> <tr> <td>≤4000</td> <td>≤5000</td> <td></td> <td></td> </tr> <tr> <td>±1.65</td> <td>±2.0</td> <td></td> <td></td> </tr> </table>				≤200	≤500	≤710	≤1120	±0.30	±0.40	±0.50	±0.65	≤1600	≤2000	≤2500	≤3150	±0.80	±0.95	±1.10	±1.35	≤4000	≤5000			±1.65	±2.0			
≤200	≤500	≤710	≤1120																																	
±0.30	±0.40	±0.50	±0.65																																	
≤1600	≤2000	≤2500	≤3150																																	
±0.80	±0.95	±1.10	±1.35																																	
≤4000	≤5000																																			
±1.65	±2.0																																			
								<p>Technical processing standards without notes according to ...JB/T2300-2011</p>																												
				T:Pulg location S:Soft zone Y:Oil hole Z:Lifting hole																																