



Notes:
 1. Raceway of inner & outer ring induction hardened. hardness: 55~62HRC
 Depth ≥ 3.5mm
 2. Inner & outer ring quenched & tempered, hardness: 207~262HB

Gear Data				Design		Check		Model							
Module	m	8	Gear heat treatment requirements		Date		Approve			Model	011.40.900		Weight	240kg	
Teeth no.	z	130	HRC			Qty	Size			Axial clearance	0.06~0.30	Name	Slewing Bearing	Qty	
Teeth pressure angle	α	20°	Precision(GB10095-88)	10	Inner ring mounting hole	30	Φ22	Radial clearance	0.06~0.30	Material	50Mn	Total 1 page		The 1st page	
Modification coefficients	x	+0.5			Outer ring mounting hole	30	Φ22	machine tolerances without notes ≤200 ≤500 ≤710 ≤1120 ±0.30 ±0.40 ±0.50 ±0.65 ≤1600 ≤2000 ≤2500 ≤3150 ±0.80 ±0.95 ±1.10 ±1.35 ≤4000 ≤5000 ±1.65 ±2.0				XUZHOU WANDA SLEWING BEARING CO.,LTD Fax: +86 516 83309366 Fax: +86 516 83915766 http://www.slew-bearing.com			
Reduction coefficients	km	0.8			Oil hole	6	M10x1	Technical processing standards without notes according to ...JB/T2300-2011							
Pitch diameter	d	1040							T:Pulg location S:Soft zone Y:Oil hole Z:Lifting hole						