

U.O.N 6.3



Notes:
1.Raceway of inner &outer ring induction hardened. hardness: 55~62HRC
Depth≥3.5mm
2.Inner & outer ring quenched & tempered, hardness：207~262HB

Gear Data				
Module	m	10	Gear heat treatment requirements	
Teeth no	z	127	_____ HRC	
Teeth pressure angle	α	20°	Precision (GB10095-88)	10
Modification coefficients	x	+0.5		
Reduction coefficients	km	1		
Pitch diameter	d	1270		

Design		Check	
Date		Approve	

	Qty	Size
Inner ring mounting hole	36	Φ22
Outer ring mounting hole	36	Φ22
Oil hole	6	M10×1

Axial clearance	0.02~0.04
Radial clearance	0.02~0.04

T:Pulg location S:Soft zone Y:Oil hole Z:Lifting hole

machine tolerances without notes

≤200	≤500	≤710	≤1120
±0.30	±0.40	±0.50	±0.65
≤1600	≤2000	≤2500	≤3150
±0.80	±0.95	±1.10	±1.35
≤4000	≤5000		
±1.65	±2.0		

Technical processing standards without notes according to ...JB/T2300-2011

Model	111.28.1120			Weight	230kg
Name	Slewing Bearing	Qty		Scale	
Material	50Mn	Total 1 page		The 1st page	

XUZHOU WANDA SLEWING BEARING CO.,LTD
XZWD®
Fax：+86 516 83309366 Fax：+86 516 83915766
http://www.slew-bearing.com